

ARTIFACT SHEET

Enter artifact number below. Artifact number is application number + artifact type code (see list below) + sequential letter (A, B, C . .). The first artifact folder for an artifact type receives the letter A, the second B, etc.. Examples: 59123456PA, 59123456PB, 59123456ZA, 59123456ZB

08051899 BA

Indicate quantity of a single type of artifact received but not scanned. Create individual artifact folder/box and artifact number for each Artifact Type.

CD(s) containing:

computer program listing

Artifact Type Code: P

Doc Code: Computer

pages of specification

and/or sequence listing

and/or table

Doc Code: Artifact

Artifact Type Code: S

content unspecified or combined

Doc Code: Artifact

Artifact Type Code: U

Stapled Set(s) Color Documents or B/W Photographs

Doc Code: Artifact Artifact Type Code: C

Microfilm(s)

Doc Code: Artifact Artifact Type Code: F

Video tape(s)

Doc Code: Artifact Artifact Type Code: V

Model(s)

Doc Code: Artifact Artifact Type Code: M

Bound Document(s)

Doc Code: Artifact Artifact Type Code: B

Confidential Information Disclosure Statement or Other Documents
marked Proprietary, Trade Secrets, Subject to Protective Order,
Material Submitted under MPEP 724.02, etc.

Doc Code: Artifact Artifact Type Code X


Other, description:

Doc Code: Artifact Artifact Type Code: Z

08/05/899

1250

The
United
States
of
America



The Commissioner of Patents
and Trademarks

Has received an application for a patent for a new and useful invention. The title and description of the invention are enclosed. The requirements of law have been complied with, and it has been determined that a patent on the invention shall be granted under the law.

Therefore, this

United States Patent

Grants to the person or persons having title to this patent the right to exclude others from making, using or selling the invention throughout the United States of America for the term of seventeen years from the date of this patent, subject to the payment of maintenance fees as provided by law.

Harry F. Manley, Jr.

Commissioner of Patents and Trademarks

Priscilla A. Fuller

Attest

NOTICE

If the application for this patent was filed on or after December 12, 1980, maintenance fees are due three years and six months, seven years and six months, and eleven years and six months after the date of this grant, or within a grace period of six months thereafter upon payment of a surcharge as provided by law. The amount, number, and timing of the maintenance fees required may be changed by law or regulation.

United States Patent [19]

Bocchi et al.

[11] Patent Number: 4,998,531

[45] Date of Patent: Mar. 12, 1991

[54] **IMPLANTABLE N-PHASIC DEFIBRILLATOR OUTPUT BRIDGE CIRCUIT**

[75] Inventors: David E. Bocchi, Vadnais Heights; Jeffrey T. Laackman, Isanti; Stanley M. Bach, Jr., Shoreview, all of Minn.

[73] Assignee: Cardiac Pacemakers, Inc., St. Paul, Minn.

[21] Appl. No.: 501,527

[22] Filed: Mar. 28, 1990

[51] Int. Cl. 5 A61N 1/00

[52] U.S. Cl. 128/419 D

[58] Field of Search 128/419 D, 419 PG, 419 P

[56] References Cited

U.S. PATENT DOCUMENTS

4,504,773 3/1985 Suzuki et al. 128/419 D
4,693,253 9/1987 Adams 128/419 D
4,840,177 6/1989 Carbonnier et al. 128/419 D
4,850,357 7/1989 Bach, Jr. 128/419 D

Primary Examiner—Francis Jaworski

Assistant Examiner—George Manuel

Attorney, Agent, or Firm—Fleit, Jacobson, Cohn, Price, Holman & Stern

[57] **ABSTRACT**

An output bridge circuit comprising four independently controlled transistors connected between first and second electrode terminals and a defibrillation capacitor. Two of the four transistors are driven by push-pull driver circuits and connected between the capacitor and the first and second electrode terminals. The remaining two transistors are connected between the first and second electrode terminals and ground terminals. By triggering one of the transistors connected to the push-pull driver circuits and one of the transistors connected between the electrode terminals and the ground terminal, a mono-phasic, multi-phasic, or sequential defibrillation pulse can be generated by activating the appropriate transistors.

5 Claims, 6 Drawing Sheets

